

## APPARATUS FOR COVERING PAYLOADS

### BACKGROUND

The shipping industry is vital to commerce in the United States and in most nations around the world. The trucking industry is one of the most important branches of the shipping industry in many countries including the United States. It is estimated that at least thirty to forty percent of all goods transported in the United States are hauled by trucks pulling flat bed trailers.

The types of materials and commodities hauled on flat bed trailers vary dramatically. Many such materials can be hauled without regard to whether such goods are exposed to inclement weather. However, it is often preferable that materials that are shipped on flat bed trailers and other modes of open transportation be protected from adverse weather conditions by a covering of some type. There are various types of coverings used in the shipping industry. One of the most common is a tarpaulin which is usually made of durable but flexible material such as vinyl or canvas. Tarpaulins can conform to many shaped and sized payloads being shipped.

However, spreading a tarpaulin over a payload on a flat bed trailer presents several problems. Manual application of a tarpaulin often begins with lifting a folded tarpaulin to the top of the payload. Workers then climb to the top of the payload, unfold the tarpaulin and spread it over the payload. Because tarpaulins are usually heavy, some workers cannot lift or maneuver tarpaulins without assistance. It is further difficult for workers to obtain complete coverage over uneven payloads by manually applying a tarpaulin, especially if they attempt to do so without assistance. The process is therefore time-consuming and inefficient. In some instances, workers injure themselves by lifting and moving the tarpaulin, which often weigh up to 200 pounds.

1 In addition, working on top of a payload often exposes workers to dangerous heights.  
2 It is well known that workers have been injured as a result of falling while climbing up or down the  
3 payload or while trying to maneuver the tarpaulin on top of the payload. It is estimated that injuries  
4 to workers while covering payloads is a significant source of worker's compensation claims and  
5 other losses in the shipping industry. There is, as a result, a need for a safe, efficient means to cover  
6 payloads that are to be shipped.

7  
8 There are presently several devices employed by those in the trucking industry for  
9 covering payloads. These include: <sup>296/100</sup>*Forsberg*, U.S. Pat. No. 3,820,840; *Chenoweth*, U.S. Pat. No. <sup>296/100</sup>  
10 <sup>296/100</sup>5,882,062; *Fenton*, U.S. Pat. No. 4,067,603; *Hardy*, U.S. Pat. No. 4,944,551; *Haddad*, U.S. Pat. No. <sup>296/100</sup>  
11 <sup>296/100</sup>5,102,182; *Pickering*, U.S. Pat. No. 4,032,186; and *McIntyre*, U.S. Pat. No. 5,713,712. However,  
12 each one of these references suffers from disadvantages, including that each requires sides or some  
13 other upright supports mounted on the trailer bed for applying and supporting a covering.

14  
15 For the foregoing reasons, there is a need for an apparatus that permits the application  
16 of a covering over a payload that can be operated by a single individual from ground level without  
17 requiring that the device be mounted on or attached to the vehicle or payload being covered. It is  
18 further an object of the present invention that it be easy to erect, mobile, and adaptable to various  
19 shapes and sizes of payloads.

## 20 21 22 SUMMARY

23 These and other objects and advantages are obtained in an apparatus for covering  
24 payloads being shipped by various modes of transportation, including flat bed trailers. The apparatus


1 comprises a movable hoist, having a retractable line, that is slidably engaged to a suspended track  
2 such that said hoist can move longitudinally over a payload positioned underneath. The apparatus  
3 further comprises a spreader bar that is attached to the retractable line of said hoist. The spreader  
4 bar has means for attaching to the leading edge of a tarpaulin or other cover that will be spread over  
5 the payload as will be described in more detail below. The apparatus is further comprised of a rod  
6 affixed in transverse fashion beneath and near one end of the track. It will be appreciated that the  
7 rod provides support to the trailing portion of the tarpaulin as the leading edge of the tarpaulin is  
8 pulled by the hoist over the payload. The hoist is powered by remote means, that can be controlled  
9 from ground level at most any position adjacent to the payload.

#### DESCRIPTION OF THE DRAWINGS

12 These and other features, aspects and advantages of the present invention will become better  
13 understood with reference to the following description, appended claims, and accompanying  
14 drawings where:

15 Fig. 1 is a three-dimensional view of an embodiment of the invention.

16 Fig. 2 is a partial three-dimensional view of the present invention in use on a flat-bed trailer.

17 Fig. 3 is a partial side view of the apparatus.  
18 

#### DESCRIPTION

20 Referring to **Figs. 1, 2 and 3**, the apparatus for covering payloads is illustrated.  
21 Although the field of application of the present invention includes providing coverings over objects  
22 being shipped by various modes of transportation, it is anticipated that the present invention will find  
23 its most widespread use in connection with covering payloads being shipped on flat bed trailers.  
24

52 The apparatus comprises a movable hoist 4, having a retractable line 5, that is slidably engaged to a suspended track 6. It will be appreciated that said track permits said hoist to move longitudinally over a payload 7 positioned underneath. The apparatus further comprises a spreader bar 8 that is attachable to said retractable line of said hoist. The spreader bar has means 9 for attaching to the leading edge of a tarpaulin 10 or other cover that will be spread over payload 7 as will be described in more detail below. In a preferred embodiment, means 9 comprises what are commonly referred to in the industry as snap shackles, or other similar devices, that contain spring loaded locking mechanisms that permit release by remote measures such as by pulling a rope properly attached to said shackle. The hoist 4 is powered by a means 11 operable from various positions, including from the ground level.

In a preferred embodiment, said track is suspended from a support structure 12. In one alternative embodiment, said support structure comprises a base 13 and a vertically extending side frame 14 rigidly attached thereto, said side frame being generally rectangular in shape and comprised of a plurality of sturdy members 15 such as steel beams connected together by welding or other fastening means. At least two arms 16, fixedly attached near the top portion of and at opposing ends of said side frame, extend perpendicularly from said frame in parallel fashion. Said track 6 is fixedly attached to said arms such that said track spans between said arms. Said track 6 should be attached to said arms a sufficient distance away from said side frame such that it could be suspended generally over the vertical centerline of payload 7 parked adjacent and parallel to said base 13.

It will be appreciated that to be most effective, said support structure should be of sufficient height to permit suspension of said track over variable sized payloads being shipped,

1 including payloads of the maximum height permitted by the Department of Transportation for the  
2 shipment of payloads on a standard flat bed trailer, which is currently 13 feet, 6 inches. In one  
3 alternative embodiment of the invention, said support structure is mobile. This can be achieved by  
4 mounting said base 13 to a standard flat bed trailer 20, thus permitting the entire apparatus to be  
5 transported and positioned at will.

6  
7 The preferred embodiment of the apparatus further comprises a rod 17 that traverses  
8 beneath track 6 on which hoist 4 moves. In the preferred embodiment, said rod is rigidly attached  
9 to said support structure at a point that is below and near one end of said track 6. It will be  
10 appreciated that rod 17 should be located at a point sufficiently high to permit clearance over most  
11 any payload. In the preferred embodiment, said rod has a circular cross section and is rotatable about  
12 its axis. As will be understood upon reference to Fig. 1, the rod supports the trailing portion of  
13 tarpaulin 10 thereby enabling the tarpaulin to be more evenly spread over payload 7 and reducing  
14 the likelihood that tarpaulin 10 will become entangled with or ensnared on the payload.

15  
16 The present invention further comprises a means for moving said hoist along said  
17 track. In the preferred embodiment, said means comprises a power source and a remote control unit  
18 11 connected thereto that is operable from ground level at any point adjacent to the payload. In one  
19 alternative embodiment, said remote control unit is connected to said hoist by wire 18. Said hoist  
20 has at least one lateral guide 19 of sufficient length to extend beyond the vertical plane defined by  
21 the outer sides of a payload. Said wire 18 runs from said hoist along and over the tip of said guide  
22 19, and then descends and is connected to said remote control unit 11. It will be appreciated that this  
23 particular configuration causes the remote control unit to move in concert with said movable hoist

1 4 as it moves over payload 7. This obtains the desirable result of allowing the operator to move at  
2 ground level along with the leading edge of tarpaulin 10 as it is spread over payload 7.

3  
4 In operation, flat bed trailer 22 with payload 7 is positioned adjacent and generally  
5 parallel to base 13 of the support structure 12 so that the centerline of payload 7 is aligned generally  
6 beneath track 6. Using remote control unit 11, the hoist 4 is maneuvered along track 6 to a point  
7 behind the rear of payload 7 and behind rod 17. Using remote control unit 11, retractable line 5,  
8 which is connect to spreader bar 8, is lowered to the ground. Spreader bar 8 then is attached by  
9 connecting means 9 to the leading edge of tarpaulin 10 that has been positioned on the ground  
10 behind the payload. Using remote control means 11, retractable line 5 is reeled in thereby raising  
11 spreader bar 8 to a level above rod 17. The hoist 4 is next powered along the track 6 pulling the  
12 tarpaulin 10 attached to spreader bar 8. As hoist 4 pulls the leading edge of the tarpaulin 10 over  
13 payload 7, rod 17 supports the trailing portion of tarpaulin 10 thus providing clearance for tarpaulin  
14 10 over payload 7. Upon reaching the front end of the payload, the hoist is stopped and the spreader  
15 bar 8 lowered, thus draping tarpaulin 10 over payload 7. <sup>so with chain</sup> Connecting means 9 are then released from  
16 tarpaulin 10. Spreader bar 8 can then be raised to permit the payload to be transported away from  
17 the apparatus.

18  
19 <sup>ps</sup> ~~It will be appreciated that, even using the present invention, it might become~~  
20 necessary for the operator to climb and work on top of the payload. For instance, the operator might  
21 wish to ensure a smooth and secure spreading of the covering over the payload. This can sometimes  
22 occur when two tarpaulins are applied to obtain complete coverage over a payload of great length.  
23 The convergence of the two tarpaulins on top of the payload might sometimes require manual  
24 smoothing or securement. To provide safety to those individuals who choose to work on top of the

1 ~~payload in such instances, one alternative embodiment of the present invention further comprises~~  
2 tether line 23 suspended in general parallel fashion to track 6. Upon ascending flat bed trailer 22,  
3 an operator secures himself by connecting a safety cable that is secured on one end to a harness worn  
4 by the operator and is slidably engaged on the other end to said tether line 23. It will be appreciated  
5 that by connecting himself to the tether line 23, an operator has substantial freedom to move around  
6 on top of the payload and is protected from falling should he trip or lose his balance.

7  
8 Although the present invention has been described in considerable detail with  
9 reference to certain preferred embodiments thereof, other versions are possible. For example, the  
10 present invention can be adapted for use on various types and sizes of flat bed trailers and other  
11 vehicles used to transport payloads, such as trains and barges. It is further envisioned that other  
12 types of structures and means can be utilized for mounting and suspending track 6. The present  
13 invention is easy to use and install and is relatively simple to manufacture. Having described the  
14 basic concept of the present invention, it will be understood by those skilled in the art that the  
15 foregoing detailed disclosure is intended to be presented by way of example only, and is not limiting.  
16 Various alternations, improvements and changes will occur and are in the scope of the present  
17 invention. Accordingly, the present invention is limited only by the following claims and  
18 equivalents thereto. The spirit and scope of the appended claims should not be limited to the  
19 description of the preferred embodiments contained herein.